

DP-530/DP-530L



Highlights at a glance:

- Easy-to-read control panel and simple drop-in paper loading
- Simple drop-in paper loading
- High-speed signature printing and extensive font and graphic capabilities
- Popular printer emulations provide compatibility

Tally DASCOM

With the Tally Dascom DP-530 series you can concentrate on your job and not on the printer.

Although the printer is up to 10% smaller and 40% lighter than comparable models, it makes no compromises. A variety of interfaces and emulations allow the use of DP-530/DP-530L in different environments.

Whether water, dust or vibrations, this printer operates reliably. Whether in the basic variant DP-530 for receipt documents or in the label version as DP 530L.

Thanks to different holders, the printer can easily install on mobile dollies or in vehicles.

Configurations:

DP-530 Standard model
 DP-530 BT Model with Bluetooth
 DP-530 WiFi Model withWiFi

• DP-530L

DP-530L BT Model with Bluetooth
 DP-530L WiFi Model with WiFi

Label model



DP-530/DP-530L

Print Method	Direct thermal printing
Resolution	203 dpi (8 Dots/mm)
Print Speed	Up to 5 inch/sec.
Barcodes	82 different versions
Download	Graphics and logos
Standard Connectivity	USB
Optional Connectivity	Bluetooth (2.0) and WiFi (802.11 b/g/n)
Bluetooth	Compatible Bluetooth 2.0 Stack
	Protocols: L2CAP, RFCOMM, SDP
	Profile: GAP, SDAP, SPP, BTLE
Emulations	Zebra CPCP and ZPL, EPL, ESC/POS, O'Neil, Printek
Printer Drivers	Windows 7/8; SDK for Windows CE/Mobile and Android; iOS unde preparation
Printer Roll Size	max. diameter 2" (5 cm) for DP-530 and 2,6" (6,6 cm= for DP-530L;
	Width 2,26 to 3,125" (5,7 to 8,0 cm)
Roll Capacity	approx. 28 m (equal 188 pcs. 6"-receipts) for DP-530
	approx. 52 m (equal 346 pcs. 6"-labels) for DP-530L
Roll Diameter	0,75" (1,9 cm)
Battery	Rechargeable 3-cell Lithium Ion (2.950 mAH)
Battery lifetime	More than 4.000" (101 m) /8 hours shift without WiFi
Charging	2 hours
Weight	0,57 kg incl. battery
Dimensions	117 x 155 x 69 mm (W x D x H) for DP-530
	117 x 155 x 79 mm (W x D x H) for DP-530L
Power Voltage	12/24 V
Temperature	-20° C to 50° C (operating), -20° C to 60° C (storing)
Humidity	10% to 90%
MTBF	10.000 hours
Approvals	CE, FCC Class B, UL, RoHS, eMark
Weight Dimensions Power Voltage Temperature Humidity MTBF	0,57 kg incl. battery 117 x 155 x 69 mm (W x D x H) for DP-530 117 x 155 x 79 mm (W x D x H) for DP-530L 12/24 V -20° C to 50° C (operating), -20° C to 60° C (storing) 10% to 90% 10.000 hours



Cigarette lighter for vehicle



Mounting plate



Mounting plate with ball



Bracket with round plate



Bracket with pole

DASCOM GB Ltd

Hart House, Priestley Road, 3
Basingstoke, Hampshire RG24 9PU, England
Tel: +44 1256 355130 – Fax: +44 1256 481400
info.gb@dascom.com – www.dascom.co.uk