



1D и  
2D



CMOS



Dual  
Laser  
Aimer



RS232



USB



IP65



Гарантия:  
2 года



**FM550**  
IVD Scanners

## Характеристики

### Wide Viewing Angle and Near Field Scanning

With a wide viewing angle, the FM550 scans both 1D and 2D barcodes from close-up, making this fixed-mount scanner a perfect choice for lab and IVD applications. It enables efficient and error-free data capture even in situations where the barcodes are not placed directly in front of the scanner.

### Effortless Integration

The FM550 features an ultra-compact design, making its integration into your IVD devices seamless. Its miniature form factor ensures a hassle-free and space-efficient installation, allowing for a smooth and efficient workflow in your laboratory automation processes.

### Image Capture

In addition to barcode scanning, the FM550 is equipped with image capture capabilities. Whether documenting sample conditions, recording experimental results, or capturing specimen images, this feature enhances data collection and

### High Precision Scanning

The FM550 is equipped with dual laser aiming, a feature that simplifies device positioning during installation. This dual laser system provides an easy and convenient way to align the scanner with the intended target, ensuring precise and accurate data capture. It streamlines the setup process for IVD integration, saving you valuable time and effort.

### Swift Data Transmission

The FM550 supports high-speed data transmission to the host system via the USB interface. This quick data transfer capability ensures that your lab automation processes remain efficient and responsive. It eliminates bottlenecks in data transfer, allowing for swift and seamless integration with your IVD devices.

### Rugged Durability

The FM550 features a rugged metal housing that is sealed to an IP65 rating. This ensures the scanner's durability, even in challenging laboratory environments. The IP65 sealing not only

## Предлагаемые области



IVD &  
Laboratory



Здравоохра-  
нение

# FM550 Технические данные

## Считывание данных

|                             |  |
|-----------------------------|--|
| 1D                          | All major 1D symbologies   |
| 2D                          | All major 2D symbologies   |
| Датчик сканера              | 800*1280 CMOS  |
| Нацеливание                 | 650nm red laser aiming LEDs*2; class 2 consumer laser product; <10mW |
| Подсветка                   | 3000K white LED  |
| Разрешение                  | ≥5mil  |
| Скорость сканирования       | 780 scans/s  |
| Диапазон декодирования      | 45-90mm  |
| Поле обзора                 | Horizontal 52°, Vertical 76.5°                                       |
| Выход луча                  | Scan window with lateral beam exit                                   |
| Минимальный контраст печати | 50%  |

## Физические характеристики

|                                      |  |
|--------------------------------------|--|
| Постоянный ток в режиме эксплуатации | 141.35mA RMS (typical), 397.54mA (max) |
| Размеры (мм)                         | 54(W)× 27.5(D)× 25.5(H) mm             |
| Корпус                               | Aluminium                              |
| Входное напряжение                   | 5VDC±5%                                |
| Интерфейсы                           | RS-232, USB                            |
| Уведомления                          | LED indicator, beeper                  |
| Потребляемая мощность                | 9W                                     |
| Вес                                  | 107g                                   |

## Условия окружающей среды

|                      |                               |
|----------------------|-------------------------------|
| Окружающее освещение | ≤5000lux                      |
| Рабочая температура  | 0°C to 50°C (32°F to 122°F)   |
| Температура хранения | -20°C to 70°C (-4°F to 158°F) |
| Влажность            | 5%~95% (non-condensing)       |
| Рейтинг IP           | IP65                          |

## Программное обеспечение

|                       |         |
|-----------------------|---------|
| Инструменты настройки | EasySet |
|-----------------------|---------|

### Newland EMEA HQ

+31 (0) 345 87 00 33

[info@newland-id.com](mailto:info@newland-id.com)

[newland-id.com](http://newland-id.com)

Не стесняйтесь обращаться к нам или к ближайшему партнеру

посетите [newland-id.com/partners](http://newland-id.com/partners)

Технические характеристики могут быть изменены без уведомления

© Newland EMEA 2023, все права защищены



# FM550 Технические данные

## Сертификаты

|              |   |
|--------------|---|
| Оборудование | CE/FCC; LED Safety: EN 62471: 2008; Laser Safety: EN 60825-1:2014+ A11: 2021, EN 50689:2021, IP65/ RoHS 2.0 |
|--------------|---|

## Гарантия

|          |         |
|----------|---------|
| Стандарт | 2 years |
|----------|---------|

### Newland EMEA HQ

+31 (0) 345 87 00 33

[info@newland-id.com](mailto:info@newland-id.com)

[newland-id.com](http://newland-id.com)

Не стесняйтесь обращаться к нам или к ближайшему партнеру

посетите [newland-id.com/partners](http://newland-id.com/partners)

Технические характеристики могут быть изменены без уведомления

© Newland EMEA 2023, все права защищены

